

TRUCK CHASSIS MZKT-802100

SPECIFICATIONS

A400M, C-5, C-17

H	<u>'</u> -	۲Н	UHI	VIAI	AC:E	DAI	Α
		_					

Wheel drive 6x6

Max. speed, km/h 60

Turning radius, m 13,5

Fuel tank capacity, I 350

Operating temperature, °C -45 ... +50

Air transportable IL-76, An-124, An-22

WEIGHT DATA

Curb chassis weight, kg 13 500
Payload, kg 20 400
Gross vehicle weight, kg 33 900
Permissible weight on axles, kg

1-3 axles 10 000 - 11 950 - 11 950

ENGINE

Number and location of cylinders V8 Power 294 kW (400 h.p.) at 1 900 min^{1} Max. torque 1 715 Nm

TRANSMISSION

Type manual Model MZKT-65151
Number of gears 9 forward, 1 reverse Gear ratio 10.8-0.79; R9.55

TRANSFER CASE

1-speed, lockable interaxle differential

DRIVING AXLES

Rigid, with central reduction gears, interaxle and cross-axle differential lock

AXLE SUSPENSION

1st axle - dependent leaf-spring 2nd and 3rd axles - dependent spring-balanced

STEERING SYSTEM

Left-hand drive Hydraulic power assisted 1st axle - steered

BRAKE SYSTEM

Drum brakes of shoe-type with pneumatic drive Dual-circuit system

TYRES

445/65 R22.5, offroad protector Central tyre inflation system (CTIS)

FRAME

Longitudinal

Equipped with front and rear towing units

CAB

Fiberglass, 2-doors, 3-seats, Equipped with ventilation and heating systems

ELECTRICAL EQUIPMENT

Nominal voltage 24 V Single-wire Batteries 2x180 Ah

OPTIONS

Powerful heater/ventilator Air conditioner Autonomous heater Tyres with Runflat system

